CS109B ML Notes for the Week of 4/17/95

Record Types

A set of field names and their associated types, surrounded by curly braces.

Example: The triples that we needed for Project 2 in CS109A (cash if out of the market and stock/cash if in) could be given the type

```
type stockRec =
    {cash_out: int, stock_in: int, cash_in: int};
```

- But different fields could have different types.

Record Values

A set of field names, each followed by = and a value of appropriate type. All are surrounded by curly braces.

Example: A possible value of type `stockRec` is

```
val myRec =
    {cash_out=500, stock_in=15, cash_in=10};
```

Extracting Field Values

The expression `#`f`(`r`)` returns the value of field f of record r.

Example:

```
#stock_in(myRec);
```
val it = 15 : int

Tuples and Records

An ugly little secret: tuples are just a shorthand for a record structure in which the fields are named 1, 2, etc.

- That's why `#`i`(`t`)` extracts the ith component from a tuple t.

Deducing a Record Type

ML cannot assume that the only fields a record has are the ones it sees. Thus, the following attempt to decide whether we are better off in or out is erroneous.

```
(* decide(r,v) determines if the cash-if-out in record
   r exceeds the value of the stock-and-cash-in, assuming
   v is the stock price *)
fun decide(r,v) =
    #cash_in(r) > v*#stock_in(r) + #cash_in(r);
```

Error: unresolved flex record in let pattern
type: { cash_in:'Y, cash_out:'Y, stock_in:'Y,' ...Z
more errors . . .

- The problem is that ML doesn't know these are the only fields of r.
- Fix by declaring the type of r somewhere, e.g.,

```
fun decide(r:stockRec,v) =
    #cash_in(r) > v*#stock_in(r) + #cash_in(r);
```

*val decide = fn : stockRec * int → bool*

Ellipses

When writing patterns involving record types, we may specify the fields in any order. We may also omit some fields by using the *ellipsis* or *wildcard symbol*, ...

- But remember that ML must be able to figure out the full set of fields somehow.

Example: A function that tests if an "in" position leaves no cash left over:

```
fun noCash({cash_in=0,...}:stockRec) = true
|   noCash(_) = false;
```

- The type `stockRec` is sufficient to tell ML what the fields are.

Matches

A *match* is an expression consisting of one or more subexpressions

pattern => expression

separated by bars.

- A match M is applied to a value v. The first pattern that matches the value determines the result as follows:

- First, any variables in the pattern are bound to values they match in v.

- Then the associated expression, which may involve variables of the patern, is evaluated, yielding the value of M applied to v.

Example: Here is a match that tells if a list has zero, one, two, or many elements:

```
nil => "zero" |
[x] => "one" |
[x,y] => "two" |
_ => "many"
```

- Warning: the above is not an expression; it is used within expressions.

Using Matches

A match M can be used to:

1. Define anonymous functions. `val f = fn` M defines f to be a function that applies M to its argument.

   - OK; so now `fn` M is no longer "anonymous," but the point is you can use `fn` M any place a function of the appropriate type is expected, without first calling it f.

Example:

```
val f = fn
        nil => "zero" |
        [x] => "one" |
        [x,y] => "two" |
        _ => "many"
f([1,2]);
```
val it = "two" : string

2. Match M can be used in a case statement. `case` v `of` M causes M to be applied to v.

Example:

```
fun f(x) = case x of
        nil => "zero" |
        [x] => "one" |
        [x,y] => "two" |
        _ => "many"
```